

PROFESSIONAL FILTRATION WASTEWATER TREATMENT

HiFlux Auto-line® filters are specially designed for automatic filtration of wastewater in treatment plants.



World leading company producing customized industrial filter solutions. Increased security, production and better profitability.



HiFlux Filtration A/S

About the Auto-line® Automatic filter

The Auto-line VLR-E filter is installed at several wastewater treatment plants and each filter has a capacity around 1.000 cubic meters of liquid per hour.

Before installation:

Cleaning manual filters regularly, high maintenance costs, downtime in production.

After installation:

Automatic process, increased productivity, minimal maintenance, no production stops.

Facts for the Auto-line® Automatic filter

HiFlux Auto-line® Filter has been designed as a compact, self-cleaning filter. The sturdy construction of the filter makes it well suited for applications in which operational reliability and dependability are essential.

Accurate filtration down to 35 micrometers [μm].

FEATURES

- **Removes unwanted particles**
High operational reliability.
- **Ensures the quality**
Increased product quality.
- **Continuous flow process**
Self-cleaning application.
- **Eliminates downtime**
Optimizing earnings.



Did you know?

That, the Auto-line filter can be used for protection of the heat exchangers in order to reuse the heat energy from the wastewater.

In this process the automatic design of the Auto-line filter is optimal for continuous operation, increased productivity and reduced maintenance costs.

Facts and regulations:

PED ATEX

CE ISO 9001

HiFlux Filtration A/S

Lundagervej 25a
8722 Hedensted

www.hiflux-filtration.com
info@hiflux.dk

Tel +45 76 74 16 60
VAT no. dk 13 45 74 76